1	2	3	4	5		6	,		8
/					REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
					A	NEW RELEASE	JLZ 09/06/23'	\sim	
4									
-				N	Notes:				
1					Product S	ize: For 0.25mm ² -10			
4					Product N	laterial:Carbon Steel,	Plastic.		
-					Crimping	tool is specially used	for installation of Cord I energy to install at site.	nd Terminals.	
-				F	Product Ni	umber Code:	energy to install at site.		
						2-33 - X X			
					03110	$2-33 - \chi$			
				No. of Concession, name			— Crimping type		
			and the second states				1: Type 1		
				A State of the second			 Plastic color RL: Red&Blue 		
	0						BL: Black&Blue		
	0	HSC8 6-4							
	3	0.25-10mm A/VG25-7							
	220 3								
	9								
	-< 01°		A REAL PROPERTY AND INCOME.						
	and a								
							-		
			and the second						
							A		
						4	A		
		175 Ref							
		1701101		•					
							Effect Reference		
. [
			GENERAL TOLE	RANCE ANGLE T	OLERANC	E PROJECTION		and Final Tanzair als C :	
					1 5.	UNITS		ord End Terminals Crim	iping 1001 6-4A Ty
			X. ±0. .X ±0.	60 X. 38 .X	±5° ±3°	SHEET SIZE	A4 SERIES	DS1162-33 SER	IES
			.XX ±0.	25 .XX	±2°				
1			DRAWING TYPE				晨翔电	子有限	一公司
					1			VY FI' L	
			SCALE	1:1 SHEFT	11 OF 3	/ 🛛 🧡			
			SCALE DRAWING NO.	1:1 SHEET C-DS1162-33-	1 OF 2 		CONNFLY EL	.ECTRONIC	

Dept	1	2			3			4		5	REV.	6 DESCRIPTION	5	Z	CHECKED	8 APPROVED	
A Qty	/									-	A A	NEW RELEASE	J	ILZ 09/06/23'		AFTROVED	A
ED 1										-							
ISO 1	1									-							
PD 1 R&D 1	1									L	Notes:						
B QA 1	1											t Size: For 0.25mm ² t Material:Carbon Ste					В
QC 1 QE 1	1		0								Crimpin	g tool is specially us e much helpful to sav	ed for in	nstallation of Cord E	End Terminals.		
nation		· • • • •		-				The second			Product	Number Code:		gy to motal at one.			
rights r modifi any forr			E T	1							DS11	62−33 − <u>X X</u> - ⊤ ⊤ .	×х	- Terminals Materia			
and its use in use in		10												B: Brass	115		С
operties uthorize				A										C: Red Copper			
sctual pr tes. Una torization														- Terminals Q'ty A: 1200 Pcs			
he intella is affilia uch righ				175 Re	of									- Crimping type			
ibited. T LY or i t constil ver of s		4		17510	51			7						1: Type 1			
is proh does no does no does no														- Plastic color			D
recipient usively t nly and constitul		E0508					10-12							RL: Red&Blue BL: Black&Blue			
an the poses or poses or		white 200pcs	E1008	E1508 E	E2508 I		red 25pcs										
other th are owr ights do			red	black	blue	gray											
a party w-how, such -		E7508	200pcs 2	250pcs 2	50pcs	50pcs	6012										E
ure to - nical kno exercise		gray 200pcs					ellow 5pcs										
y disclos d techi eled here elays to						2.	opes										
ntial. An rets, an is provid res or d		1920	and a	TANDA 14		-10											
confide confide rade sec propertie						891-1	2										
and is rights ti discretio					207	86	510										F
Co., Ltd ts. copy All inte its own		2345 P	11/3				591										
sctronic s paten johts at	x																
NFLY Elect ademarks. from COI operty righ				or V Pc		Mr 2	BY										
d to, tro consent ctual pro		VERNE AU	1200	7-16		1-1-	EC.	3									G
n is fror ot limite written s intelle							G	ENERAL	TOLERANCE	ANGLE 1	OLERAN	NCE PROJECTION			h End Torminala Ori-	iping Tool Kit 6-4A Ty	
ed herei g but nu force it								Х.	±0.60	×.	±5°	UNITS	n	nm			he
n provid- includin ted withc	,							.× .××	±0.38 ±0.25	.X .XX	±3° ±2°	SHEET SIZE		4 SERIES	DS1162-33 SEF		
formation prohibit CONNFLY									TYPE CUST				晨	: 翔 电	子有限	良公司	Н
The inf contained is strictly manner. (SCALE DRAWING	1:1 NO. C-DS	SHEET S1162-33	2 OF 			NNFLY EL	ECTRONIC	CO. LTD	
	1	2			3			4		5		6	5		7	8]